

Coater Machine

Coater Machine is the new coating range that builds on the proven Umang technology and its benefits. Similar design of process pan, spray nozzle and air distribution ensures that process and validation machine to machine there is no difference to the coating process. This unique design of process perforated pan, spray nozzles and systems and air blowers makes the not only a perfect Coater machine but also an ideal machine with various options for Coater Machine too.

The outstanding feature of the Coater Machine is the integrated and CIP optimized design. Connections, cabling and supplies are completely integrated, covered and sealed so the outside of the machine is smooth and very easy to clean. The innovative discharge valve design and optimized seals inside the bowl allow for CIP. As a result of this the our Coater Machine is highly flexible, quick product changeover increases productivity and cost effectiveness.

The Coater Machine ranges from 50 gms. batch capacity to 300 Kgs./batch featuring through the wall design and movable head, allowing operation with platform and dust-free discharging via a linked mill directly into an IBC. The Coater Machine can be stand-alone or linked to a tableting or blister machine to form an integrated system.



Standard Features for Coater Machine :

- Uniform scalable perforations from a laboratory scale machine to a production scale machine.
- No seals in direct contact with the product
- Perfect cGMP-design: smooth covering, no external tubing and piping allowing easy cleaning
- Completely integrated full opening side discharge: perfect discharge of difficult products
- Through the wall installation: minimum space required in GMP area
- User-friendly operator-machine interaction via graphical operator panel 12" Industrial PC software with PROCESS + range of software which helps interlinking all plant equipments to a single system.
- Flexibility (processes and products) for coating.
- Insulated process chamber and equipment.

Standard Features for Coater Machine :

- Explosion proof design
- Automatic cleaning (WIP/CIP) of entire system
- 21 CFR part 11 certified controls.
- ADVANCE PROCESS + for easy and automated granulation control
- Total containment through up- and downstream split valves and flexible isolation systems.
- Integration with mill and/or fluid bed possible: perfect closed link for dust-free operation
- Video monitoring of the process
- Liquid addition system (peristaltic pump / pressure vessel)
- Product feeding both by gravity or vacuum loading system directly from the containers
- Validation documentation and assistance based on GAMP

Technical Specifications for Coater Machine :

MODEL	PAN DIA (mm)	BLIM VOLUME (L)
-------	--------------	-----------------

Coater Machine - 30	300	4.6
Coater Machine - 50	500	18
Coater Machine - 100	1000	105
Coater Machine - 130	1300	225
Coater Machine - 150	1500	350
Coater Machine - 170	1700	550
Coater Machine - 200	2000	900

Umang Pharmatech Pvt. Ltd.

Survey No. 146, H. No.1 (PT), Vasai Phata Highway Junction, Pelhar, NH8, Vasai (E) - 401 208, Maharashtra, India.

Tel: 022 - 30018900 & 30018915 - 98 | Fax: 022 - 30018908 & 30018913 | Email: umang@umangpharmatech.com

Equipments for Pelletization & Granulation: www.umangpharmatech.com | Personal care ingredients & Bakery decoration products: www.umangpharma.com | Pharmaceutical and Nutraceutical pellet products: www.umangpharmaceuticals.com