

Fluidized Dryer

Fluidized Dryer is the new drying range that builds on the proven Umang technology and its benefits. Similar design of distribution plate, nozzles and continuous working filter bags ensures that process and validation wise there is no difference to the drying process. This unique design of plates, nozzles and filters makes the not only a perfect drying system but also an ideal machine for Fluidized Dryer applications.

The outstanding feature of the Fluidized Dryer range is the integrated and CIP optimized design. Connections, cabling and supplies are completely integrated, covered and sealed so the outside of the machine is smooth and very easy to clean. The innovative discharge valve design and optimized seals inside the bowl allow for CIP. As a result of this the our Fluidized Dryer is highly flexible, quick product changeover increases productivity and cost effectiveness.

The Fluidized Dryer ranges from 1 to 1500 liters featuring through the wall design and movable head, allowing operation with platform and dust-free discharging via a linked mill directly into an IBC. The Fluidized Dryer can be stand-alone or linked to a high shear mixer for granulation or a extrusion and spheronization system to form an integrated system.



Standard Features for Fluidized Dryer :

- Distribution plate available in plain uniform perforations.
- Swirl design of plates possible as a option.
- Perfect cGMP-design: smooth covering, no external tubing and piping allowing easy cleaning
- Completely integrated full opening side discharge: perfect discharge of difficult products
- Through the wall installation: minimum space required in GMP area
- User-friendly operator-machine interaction via graphical operator panel 12" Industrial PC software with PROCESS + range of software which helps interlinking all plant equipments to a single system.
- Flexibility (processes and products) for wet granulation.
- Different up plate and down plate configurations for fluid bed coating applications.

Standard Features for Fluidized Dryer :

- Explosion proof design
- Automatic cleaning (WIP/CIP) of entire system
- 21 CFR part 11 certified controls.
- ADVANCE PROCESS + for easy and automated granulation control
- Jacketed / insulated liquid tank
- Total containment through up- and downstream split valves and flexible isolation systems.
- Integration with mill and/or fluid bed possible: perfect closed link for dust-free operation
- Video monitoring of the process
- Liquid addition system (peristaltic pump / pressure vessel)
- Product feeding both by gravity or vacuum loading system directly from the containers
- Validation documentation and assistance based on GAMP

Technical Specifications for Fluidized Dryer :

MODEL	Fluidized Dryer - 50	Fluidized Dryer 125	Fluidized Dryer 250	Fluidized Dryer 500	Fluidized Dryer 750	Fluidized Dryer 1000	Fluidized Dryer 1500
Batch Capacity (Ltrs.)	56	125	265	525	800	1100	1640

Umang Pharmatech Pvt. Ltd.

Survey No. 146, H. No.1 (PT), Vasai Phata Highway Junction, Pelhar, NH8, Vasai (E) - 401 208, Maharashtra, India.

Tel: 022 - 30018900 & 30018915 - 98 | Fax: 022 - 30018908 & 30018913 | Email: umang@umangpharmatech.com

Equipments for Pelletization & Granulation: www.umangpharmatech.com | Personal care ingredients & Bakery decoration products:
www.umangpharma.com | Pharmaceutical and Nutraceutical pellet products: www.umangpharmaceuticals.com