

Rapid Granulator

Rapid Granulator is the new pelletization range that builds on the proven Umang technology and its operational benefits. Similar design of loss in weight twin screw feeder, rotating plate and spray gun for liquid ensures that process and validation wise there is no difference to the layering process from a laboratory scale to a production scale. This unique design of twin screw feeder, plate and spray nozzle makes the not only a perfect Rapid Granulator machine but also an ideal machine suited for fast pelletization.

The outstanding feature of the Rapid Granulator range is the integrated and CIP optimized design. Connections, cabling and supplies are completely integrated, covered and sealed so the outside of the machine is smooth and very easy to clean. The innovative discharge valve design and optimized seals inside the bowl allow for CIP. As a result of this the our Rapid Granulator is highly flexible, quick product changeover increases productivity and cost effectiveness.

The Rapid Granulator capacity ranges from 500 gms to 120 Kgs./batch featuring through the wall design and movable head, allowing operation with platform and dust-free discharging via a linked mill directly into an IBC. The Rapid Granulator can be stand-alone or linked to a fluid bed coating system for further sustained release coating or enteric coating to form an integrated pelletization system.



Standard Features for Rapid Granulator :

- Various designs of chequered plate starting from 1mm chequered size.
- Plate and shaft seals not in direct contact with the product
- Perfect cGMP-design: smooth covering, no external tubing and piping allowing easy cleaning
- Completely integrated full opening side discharge: perfect discharge of difficult products
- Through the wall installation: minimum space required in GMP area
- User-friendly operator-machine interaction via graphical operator panel 12" Industrial PC software with PROCESS + range of software which helps interlinking all plant equipments to a single system.
- Flexibility (processes and products) for spheronization or pellet line / pelletization process

Standard Features for Rapid Granulator :

- Explosion proof design
- Automatic cleaning (WIP/CIP) of entire system
- 21 CFR part 11 certified controls.
- ADVANCE PROCESS + for easy and automated granulation control
- Jacketed / insulated bowl
- Total containment through up- and downstream split valves and flexible isolation systems.
- Integration with mill and/or fluid bed possible: perfect closed link for dust-free operation
- Video monitoring of the process
- Product feeding both by gravity or vacuum loading system directly from the containers
- Validation documentation and assistance based on GAMP

Technical Specifications for Rapid Granulator :

MODEL	FULL CAP	WORK CAP
Rapid Granulator - 30	70	30
Rapid Granulator - 50	120	50
Rapid Granulator - 100	240	100
Rapid Granulator - 200	455	200
Rapid Granulator - 300	670	300
Rapid Granulator - 400	850	400
Rapid Granulator - 500	1050	500
Rapid Granulator - 600	1280	600

Umang Pharmatech Pvt. Ltd.

Survey No. 146, H. No.1 (PT), Vasai Phata Highway Junction, Pelhar, NH8, Vasai (E) - 401 208, Maharashtra, India.

Tel: 022 - 30018900 & 30018915 - 98 | Fax: 022 - 30018908 & 30018913 | Email: umang@umangpharmatech.com

Equipments for Pelletization & Granulation: www.umangpharmatech.com | Personal care ingredients & Bakery decoration products:

www.umangpharma.com | Pharmaceutical and Nutraceutical pellet products: www.umangpharmaceuticals.com